

EASY COAT ADVANCED FORMULA ALL PURPOSE WALL PUTTY



FEATURES & BENEFITS

USG Middle East All Purpose Wall Putty provides an excellent quality thin underlayment solution used to repair walls and ceilings as crack filler.

All Purpose Wall Putty provides very smooth surface finish does not require sanding and ready for paint and decorative coatings.

USG Middle East All Purpose Wall Putty is a premium-grade filler and base for use before painting or decorating. All Purpose Wall Putty by USG Middle East is designed to smooth and fill cement and gypsum walls and ceilings. Excellent quality thin underlayment solution used to repair walls and ceilings as crack filler.

All Purpose Wall Putty provides very smooth surface finish does not require sanding and ready for paint and decorative coatings. Complies with ASTM C475.

- Repair walls as filling compound.
- Excellent for use in Skim Coating.
- For use over Concrete and Gypsum Walls and Ceilings.
- Provides very smooth surface finish and does not require sanding.
- Dries to a Fine White Finish.



PATCHING



SKIMMING



HAND &
MECHANICAL
TOOLS



TIME AND
COST
SAVINGS

PREPARATION FOR SURFACE

Characteristics of USG Middle East All Purpose Wall Putty include excellent bond, superior adhesion to plastered surfaces, resistance to flaking and chipping, and a fine white finish when dry.

Surface must be clean, dry, free from swelling, dirt, dust and non-rusted. Use flexible blade to remove all loose materials from surface. Grind off any major surface imperfections prior to use.

MIXING

Before use, condition USG Middle East All Purpose Wall Putty and all substrates at temperatures between 13-35°C for at least 24 hours.

Mix contents lightly and perform test application. If needed, incrementally mix in very small amounts of clean water (250ml or less) and mix again.

APPLICATION ON SUBSTRATE

Never apply when the temperature is below or expected to fall below 13°C. Use a wide drywall knife, joint knife, trowel or flexible steel blade to apply first coat.

Level and smooth surface before apply All Purpose Wall Putty. After putty has fully dried (usually 6 hours or longer, depending on conditions) apply second coat, Usually All Purpose Wall Putty.

Interior Wall Putty does not request sanding after application and dry; but in case if the wall conditions require to sand to a smooth, level surface using 120 grit or finer sand paper. Remove sanding dust with a brush or damp cloth before adding additional coats or decorating.

DRYING TIME

Allow to fully dry before adding successive coats. Drying time varies based on the thickness of the putty and environmental conditions. Drying time usually is 6-8 hours, depending on conditions.

DECORATING

For excellent decorating finish use Sheetrock® Brand Tuff Hide™ Primer Surfacer before applying finish paint. Use of a primer increases the coverage rate of the finish paint and provides a finer finish. Strictly follow manufacturer's instructions for primers or paints and consult them for help with decorating problems.

PRODUCT DATA

	USG Middle East All Purpose Wall Putty
Color	White
Packaging	Net 20kg re-sealable pail
Skimming Coverage	25m ² (based on 1mm thickness)
Drying Time	6-8 Hours
Shelf Life	18 months

LIMITATIONS

- The application of USG Middle East All Purpose Wall Putty at interior temperatures less than 10°C is not recommended. Under cold or wet weather conditions, allow more than 24 hours for thorough drying.
- When diluting USG Middle East All Purpose Wall Putty do not vigorously over mix as this will introduce entrapped air which can result in surface imperfections.
- Do not apply USG Middle East All Purpose Wall Putty over joints that are not thoroughly dry; pinholes may result.
- Consume an opened pail within 48 hours.

STORAGE OF MATERIAL

Store inside in a dry location at room temperature, between 13-35°C. Protect from freezing, extreme heat, and exposure to direct sunlight. Keep container tightly sealed.

PRECAUTIONARY STATEMENT

- Dust from this product contains silica. Prolonged inhalation may be harmful to health.
- Ensure adequate ventilation. Wear eye protection and an approved disposable respirator which conforms to AS1716: 2012 Type P1 or P2.
- If dust or paste causes irritation use impervious PVC, nitrile or rubber gloves. Wash exposed skin after handling. If product gets into the eyes, wash thoroughly with clean water.
- Do not ingest contents of package. If ingested, seek medical advice immediately.
- Keep contents out of reach of children.
- Be conscious of the environment. Dispose of empty packaging in a responsible manner.
- Follow safe lifting instructions on the product label.

REFERENCES

For further health and safety instructions, refer to the Safety Data Sheet (SDS) for this product, available from your USG Middle East sales office or **USGme.com**

Disclaimer:

Information contained in this document is subject to change without prior notice due to our ongoing product development. We recommend referring to the website **usgme.com** for the most up-to-date and accurate product information.

©2023 Factory of USG Middle East LTD. Co.
All rights reserved.

