





## USG MIDDLE EAST CERAMIC CLADDING ACCESS PANEL



## INSTALLATION AND FIXING

## **FEATURES & BENEFITS**


**USG Middle East Ceramic Cladding Access Panel** are produced especially for use in tiled areas, such as bathrooms, toilets and kitchens. Two layers of gypsum plasterboard (2x125mm) in higher quality in accordance with EN 520 are used upon request. The panel cover surface can be tiled with various standard tiles. In the process, an outward-facing visual joint spacing of 3-4mm is maintained. At the bottom in the mounting frame there is a silicon spacing profile used as a support and seal for the panel cover that prevents the sinking of the panel cover. A safety steel rope guarantees the catching of the flap cover with every opening. After unlocking the carabiner, the flap lid is completely removable. For flaps with a height greater than 650mm and large weight two additional safety arms are available as a catch between flap lid and mounting frame.


- Can be tiled with all common tiles
- Safe and simple handling with strong components & securing elements
- · Maintenance free


Easy in installation of the aluminium frame in the opening (approx. 5mm larger than the installation dimensions) in the wall. When installing, the fasteners must be aligned towards the top. Screwing together takes place from the front right through the plasterboard and the installation frame.

## **AVAILABLE DIMENSIONS**

Size Length x Width (A x B)	Installation Size Length x Width (A1 x B1)*	External Dimensions Length x Width (A2 x B2)	Clear Opening Length x Width (A3 x B3)	Tileable Area Length x Width (A4 x B4)	Depth (T1 x T2)	Weight (KG) **
300 x300	298 x 298	338 x 338	280 x 280	281 x 281	26/41	2.6
400 x 400	398 x 398	438 x 438	380 x 380	381 x 381	26.41	4.6
500 x 500	498 x 498	538 x 538	480 x 480	481 x 481	26/41	5.5
600 x 600	598 x 598	638 x 638	580 x 580	581 x 581	26.41	9







- Information contained in this
  document is subject to change

  \* Structural opening = installation size (A1, B1) + 5mm
  without prior notice due to our

  \*\* Weight = compagent weight (without packaging)
  - \*\* Weight = component weight (without packaging)
    Sizes up to 500mm with safety rope and carabiner in the middle
    (without safety arms).



Disclaimer:



ongoing product development. We

recommend referring to the website

**usgme.com** for the most up-to-date and accurate product information.

