

USG MIDDLE EAST SHAFTWALL ACCESS PANEL - HEAVY DUTY



INTENDED FOR

FEATURES & BENEFITS

- Metal Frame
- Fire Rated Plasterboard and fire rated hinges
- Intumescent paint
- Simple wall installation through mounting claws

APPLICATION

- For shaftwall, plumbing walls and brick wall installation
- With mounting claws for simple wall installation
- Tested of fire resistance class 30 minutes, 90 minutes and 120 minutes according to EN 1364-1 and EN 1634-1
- Certified by EN 13501-2
- Up-to 40dB Acoustic performance in sound attenuation

Length X Width (Nominal)	Length X Width (Service)	44.5 mm (EI30)	66.5 mm (EI90/EI 120_)
300 x 300	300 x 300	•	•
300 x 600	300 x 600	•	•
500 x 500	500 x 500	•	•
600 x 600	500 x 500	•	•
600 x 1200	500 x 1100		•

MATERIALS

Description	Material	Specification
Frame components	Steel / GKF	DX51D+Z275 MA / GKF
Fire bulkhead	Fire Rated Plasterboard	GKF
Intumescent	Foamed intumescent	
Lock, hinge	Steel	
Drywall screws	Steel	

MAINTENANCE

- Visual Inspection
- Function
- Cleanness
- Completeness
- Damage
- Condition of the seal

Disclaimer:

Information contained in this document is subject to change without prior notice due to our ongoing product development. We recommend referring to the website usgme.com for the most up-to-date and accurate product information.

©2023 Factory of USG Middle East LTD. Co.
All rights reserved.