









FEATURES & BENEFITS

- Aluminum Frame
- Resistant to moisture, mold and mildew plasterboard panel
- Designed for smoke and draft control
- High acoustic performance
- All-round lip seal
- · Safety catch on both sides
- · Hidden snap

INTENDED FOR

- For wall and ceiling installation (not to be exposed to walking/traffic loads)
- Suitable for healthcare use
- If installed in walls the lock is aligned to the ceiling
- Tested for smoke tightness with reference to DIN 18095-2
- Tested for air permeability with reference to EN 1026
- Up-to 35dB in Sound attenuation performance

APPLICATION

Length X Width (Nominal)	Length X Width (Service)	1 x 15 mm	2 x 12.5 mm
300 x 300	237 x 247	•	•
400 x 400	337 x 347	•	•
500 x 500	437 x 447	•	•
600 x 600	537 x 547	•	•
800 x 800	537 x 747	•	•

MATERIALS

Description	Material	Specification
Frame components Fixing brackets Snap holder	Extruded sections, anodizing quality	Al Mg Si 0.5 F22
Corner connector Scissor-type catch arm Limiting plate	Slit strip steel, sheet steel, fully galvanized	DC01 AM 1.5 mm
Spacer Drilling template	Slit strip steel, sheet steel, galvanized	DX51D/Z275 1.0 mm
Plasterboard Lock	Moist room GP boards Steel / plastic	
Seal Drywall screws	Hollow chamber seal Steel	EPDM

MAINTENANCE

- Visual Inspection
- Function
- Cleanness
- Completeness
- Damage
- · State of sealing gasket

Disclaimer:

Information contained in this document is subject to change without prior notice due to our ongoing product development. We recommend referring to the website **usgme.com** for the most up-to-date and accurate product information.

©2023 Factory of USG Middle East LTD. Co. All rights reserved.



