CELEBRETTO® CLIP-IN METAL CEILING



FEATURES & BENEFITS

- Concealed ceiling design.
- Wide range of standard perforation patterns.
- Wide range of optional wooden patterns.
- Durable and washable polyester powder finish.
- Robust and easy to clean.
- High sound absorption and sound attenuation.
- Environmentally friendly and recyclable.

APPLICATIONS

- Interior and exterior applications
- Transportation & airports
- Educational
- Healthcare
- Commercial buildings
- Hi-Rise & offices
- Financial & banking
- Malls & residential
- Kitchen & dietary
- Laundry



Frequency, Hz				1000	2000		NRC*					
A1 Pattern** with Acoustic Fleece	0.70	0.95	0.75	0.75	0.80	0.80	0.75					
A1 Pattern** with Infill***	0.70	0.90	1.0	1.0	1.0	1.0	1.0					

- * Calculated to ASTM C 423-01 ** A1 Pattern: Diagonal Pattern. Hole Size Dia: 1.8mm, Open Area: 20% *** Infill: Acoustic Fleece and 30mm Soft Fiber with Aluminium Foil



CLIP-IN METAL CEILING











GRID PROFILE OPTIONS

Spring T



SPECIFICATION DETAILS

Clip-in Metal Ceiling by USG ME meets the requirements in accordance with ASTM C635, ASTM C636, ASTM C423 and ASTM

Material Classification

Galvanized Steel: Type V Aluminium: Type VII Stainless Steel: Type VI Pattern: A, C, G

Panel Size

300 x 300mm, 300 x 1200mm, 300 x 1500mm, 600 x 600mm, 600 x 1200mm, 1200 x 1200mm

Panel Thickness

0.6 to 1.4mm

Panel Height

10mm, 20mm

Edge Detail Trim

Beveled edge: 600 x 600mm, 600 x

Square edge: All other panel configuration

Light Reflectance Coefficient [LR] Based on the finish color, Up to 0.82

Standard colors are RAL 9016, RAL 9006 and RAL 9010.

Other RAL colors are available upon request. Wooden patterns are available upon request

Surface Burning Characteristics per ASTM E 84

Class A

Infill Options

Plain

Acoustic Fleece

Acoustic Fleece and Glass Wool Acoustic Fleece and Mineral Fiber


Washability / Scrubbability as per ASTM D4828 & D2486

Exceeds 1000 Wash/Scrub Cycles without surface break or the extent of abrasion

Relevant LEED® Credit

EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

ITEM CODIFICATION




CLIP-IN METAL CEILING ACOUSTICAL PERFORMANCE

USG Middle East supplies metal ceiling panels with a range of acoustical performance to meet the needs of all kinds of projects. A variety of sound-absorbing backing options are available with performance up to 1.0 NRC and 34dB CAC. Consult with the USG Middle East technical team for further guidance.

PATTERN	OPEN AREA%	CELEBRETTO® METAL CEILING INFILL OPTIONS	CAC	
A1	20%	Acoustic fleece	-	0.75
A1	20%	19mm Soft Fiber infill	-	0.90
A1	20%	15mm Mineral Fiber infill	32	-
A1	20%	Acoustic fleece with 30mm Stone Wool & 19mm Mineral Fiber infill	32	0.90
A1	20%	Acoustic fleece with 25mm Glass Wool & 12mm Gypsum infill	30	0.85
A1	20%	Acoustic fleece with 30mm Stone Wool & Aluminum Foil	34	1.00
B2	16%	Acoustic fleece	-	0.60
15D	22%	Acoustic fleece	-	0.60
15D	22%	Acoustic fleece with 30mm Stone Wool & Aluminum Foil	30	0.80
15E	11%	Acoustic fleece	-	0.65
15E	11%	Celebretto Metal Ceiling with acoustic fleece and 30mm Stone Wool & Aluminum Foil	27	0.80
7E	1%	Celebretto Metal Ceiling with acoustic fleece	-	0.65
7E	1%	Celebretto Metal Ceiling with acoustic fleece and 30mm Stone Wool & Aluminum Foil	26	0.90

- · A1 Pattern: Diagonal Pattern, Hole Size Dia 1.8mm • B2 Pattern: Even Pattern, Hole Size Dia 2.5mm
- 15D Pattern: Diagonal Pattern, Hole Size Dia 1.5mm
- 15E Pattern: Even Pattern, Hole Size Dia 1.5mm
- 7E Pattern: Even Pattern, Hole Size Dia 0.75mm



^{*} Additional backer options available for NRC and CAC enhanced total acoustical performance

INFILL OPTIONS*

Notice:

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to usgme.com for the updated products information document.

©2023 Factory of USG Middle East LTD. Co. All rights reserved.

